

Product Family
Max Single-Use Earplug





Highest attenuation in single-use earplugs

[Learn more about our products at howardleight.com](http://howardleight.com)

>



Product Numbers & Ordering Information

	Product Numbers	Details
	MAX-30	Max - corded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
	MAX-1	Max - uncorded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
	MAX-LS4	Max - uncorded bulk refill for Leight Source 400 SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
	MAX-1-D	Max - uncorded bulk refill for Leight Source 500 SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.

Overview

Key Features

- The world's most-used polyurethane foam earplug
- Bell shape delivers maximum in-ear comfort
- Contoured design easier to insert, resists tendency to back-out of ear canal
- Polyurethane foam enhances comfort, especially for long-term wear
- Smooth, soil-resistant closed cell-foam skin prevents dirt build-up
- Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time, waste and space

Recommended Industries/Use

Max Single-Use Earplug

Hazards Agriculture • Chemical • Construction • Fire Protection • Forestry • Government
• Law Enforcement • Manufacturing • Medical • Military • Mining • Municipal Services
• Noise • Oil and Gas • Pharmaceutical • Steel and Metals • Transportation • Utilities • Welding

Regulations

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)
- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EC Directive/PPE
- Category II - EC Category/PPE
- EN 352-2:2002 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)
- NR 15 - Security and Health of Work, Annexes 1 and 2, n°3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)
- 9001:2008 - ISO

Historical Brand

Howard Leight

Specifications

Color

- Coral

Shape

- Bell

Material

- Polyurethane Foam

Packaging Options

- Polybag • Paper Bag • Bulk Refill for Leight Source 400 or Leight Source 500 Dispenser

Cord Options

- Uncorded • Polycord

NRR

- 33

Canada Class

- A(L)

SNR

- 37

SLC80

- 26 dB / Class 5

EU Certifications

- European Directives – 89/686/EEC
- EC Category PPE – Category II
- Standards – EN 352-2:2002
- EC Certification Number – 1219
- EC Attestation Number – 040366
- Laboratory – INSPEC
-

AUS Certifications

- Standardsmark License #1579

Certifications

EU Certificate - Max

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Secured/Hearing_Protection/Earplugs/20038/1033.aspx

EU Certificate - Max

EU Certificate - Earplugs

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Secured/Hearing_Protection/Earplugs/42685/1033.aspx

EC Declaration of conformity The manufacturer SPERIAN HEARING PROTECTION, LLC, 7828 Waterville Rd. San Diego, CA 92154 United States declares that the Personal Protective Equipment (PPE) items listed below, conform with the provisions of Council Directive 89/686/EEC and, where applicable, with the national standard, tr

Literature & Documents

EU Certification Report - Max

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Secured/Hearing_Protection/Earplugs/20052/1033.aspx

EC Attestation Report - Max

MAX 1 Max Earplugs AUSNZ

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294998652/1033.aspx

 R-01110

DOC2655 HEAR AFF Earplug Fit 508x800 GBd

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996679/1033.aspx

DOC2653 HEAR AFF Earplug Fit 508x800 SPa

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996680/1033.aspx

DOC2654 HEAR AFF Earplug Fit 508x800 FRa

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996681/1033.aspx

Hearing Thermometer POST AU

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996746/1033.aspx

M1Rifle 161 dB Fireworks 162 dB Handgun 166 dB Apollo Lift-Off 188 dB Shotgun 170 dB Artillery Fire 162 dB Firecracker 150 dB Balloon Pop 157 dB Jet Engine Take-Off 150 dB Engine Backfire 140 dB Bicycle Horn 143 dB Dynamite Blast 140 dB Pig Squeal 130 dB Jackhammer 130 dB Auto Racing 130 dB Oxygen Torch 121 dB Hammer o

Earplug Fitting Poster - AUS

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/24934/1033.aspx

POST14 Care and Maintenance

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294997025/1033.aspx

CARE AND MAINTENANCE Single-Use Earplugs Inspect Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness —discard immediately if compromised. Discard For proper hygiene, discard Single-Use earplugs after use. Hygiene To maintain hygiene standards, Single-Use earplugs should be discarded at

Training & Proper Use

1. With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
2. Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
3. Hold for 30 – 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.
4. Proper Fit – If either or both earplugs do not seem to be fitted properly, remove the earplug and reinsert.

Max Single-Use Earplug

5. Removal – Gently twist earplug while slowly pulling in an outward motion for removal.
6. Acoustical Check – In a noisy environment, with earplugs inserted, cup your hands over your ears and release. Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

Additional Information

CARE + MAINTENANCE

- INSPECT – Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness—discard immediately if compromised.
- DISCARD – For proper hygiene, discard Single-Use earplugs after use.
- HYGIENE – To maintain hygiene standards, Single-Use earplugs should be discarded at the end of every shift.

RELATED PRODUCTS