Honeywell Safety Products Australia / NZ Partners Where To Buy



Product Family X-Treme Tapered design for comfort, protection

Learn more about our products at howardleight.com



Q

Product Numbers & Ordering Information

>

	Product Numbers	Details
 <!--</td--><td>1006717</td><td>X-Treme - corded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.</td>	1006717	X-Treme - corded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
(=+60) ≠€±±1	1006716	X-Treme - uncorded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
(=++6# #€₩₿	1006188	X-Treme - uncorded bulk refill for Leight Source 400 SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
(=+00 ≠€ <u>₩</u> ()	1006821	X-Treme - uncorded Leight Source 100 Hand Dispenser SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.

Overview

Key Features

- Comfortable earplug with high attenuation
- Brightly coloured offering high visibility and worker compliance
- Smooth tapered shape for easy insertion and removal
- Corded version helps to guard against the earplugs falling onto the floor
- Conveniently sized hand dispensing option for easy accessibility
- Wall or bench top dispenser provides a refillable option for the whole work area

Recommended Industries/Use

Page 1 of 3 © Honeywell International Inc.

Hazards uction • Manufacturing

Noise

Regulations

- NOHSC: 1007 (2000) National Standard for Occupational Noise (AUS/NZ)
- NR 15 Security and Health of Work, Annexes 1 and 2, n°3.214/1978 Occupational Noise Regulations (BR)
- ANSI S12.6/1997 Method B Attenuation Test Protocol (BR)
- 9001:2008 ISO

Historical Brand

Howard Leight

Specifications

Color

Orange

Shape

Bullet

Material

• Polyurethane Foam

Packaging Options

• Polybag • Bulk Refill for Leight Source 400 or Leight Source 500 Dispenser

Cording Options

Uncorded • Polycord

SLC80

• 26 dB / Class 5

Literature & Documents

VeriPro AUSNZ

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996760/1033.aspx

► ► VeriPROTM WHAT IS VERIPRO? VeriPRO is a testing technology that makes it easy to get an accurate 'real world' picture of the attenuation that an employee is getting from their earplugs at their workplace. WHY IS SUCH A TEST NESSECARRY? Whilst the SLC80 rating is a good indicator of the performance of a given earpl

Earplug Fitting Poste AU

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996741/1033.aspx

Earplug Fitting Instructions Keys to Successful Hearing Protection with Earplugs Wear Read and follow all earplug fitting instructions. Selection Avoid overprotection in minimal noise environments – in selecting the best earplug for your situation, consider noise levels and your need to communicate with co-workers or h

Hearing Thermometer POST AU

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996746/1033.aspx

M1Rifle 161 dB Fireworks 162 dB Handgun 166 dB Apollo Lift-Off 188 dB Shotgun 170 dB Artillery Fire 162 dB Firecracker 150 dB Balloon Pop 157 dB Jet Engine Take-Off 150 dB Engine Backfire 140 dB Bicycle Horn 143 dB Dynamite Blast 140 dB Pig Squeal 130 dB Jackhammer 130 dB Auto Racing 130 dB Oxygen Torch 121 dB Hammer o

Earplug Fitting Poste AU

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996741/1033.aspx

Earplug Fitting Instructions Keys to Successful Hearing Protection with Earplugs Wear Read and follow all earplug fitting instructions. Selection Avoid overprotection in minimal noise environments – in selecting the best earplug for your situation, consider noise levels and your need to communicate with co-workers or h

POST14 Care and Maintenance

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294997025/1033.aspx

X-Treme

CARE AND MAINTENANCE Single-Use Earplugs Inspect Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness —discard immediately if compromised. Discard For proper hygiene, discard Single-Use earplugs after use. Hygiene To maintain hygiene standards, Single-Use earplugs should be discarded at

Training & Proper Use

- 1. With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
- 2. Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
- 3. Hold for 30 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.
- 4. Proper Fit If either or both earplugs do not seem to be fitted properly, remove the earplug and reinsert.
- 5. Removal Gently twist earplug while slowly pulling in an outward motion for removal.
- Acoustical Check In a noisy environment, with earplugs inserted, cup your hands over your ears and release. Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

Additional Information

CARE + MAINTENANCE

- INSPECT Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness—discard immediately if compromised.
- DISCARD For proper hygiene, discard Single-Use earplugs after use.
- HYGIENE To maintain hygiene standards, Single-Use earplugs should be discarded at the end of every shift.

RELATED PRODUCTS

Honeywell International Inc.